

Safety Data Sheet for 455

1. IDENTIFICATION OF PRODUCT and COMPANY

PRODUCT NAME - CONCEPT CONTOUR TYRE TREATMENT

PRODUCTS COVERED - 455

INTENDED USE - For professional use only. For Professional Use ONLY.

SUPPLIER - Concept Chemicals & Coatings P.O. Box 9, Bramhall, Stockport, Cheshire. SK7 1JF

Emergency Tele. - 0161-335-0213

2. COMPOSITION/INFORMATION of INGREDIENTS

25 - 50 % DISTILLATES (PETROLEUM), HYDROTREATED LIGHT

Symbols Xn,N Risk Phrases 51/53, 65

10 - 25 % SOLVENT NAPHTHA (LIGHT AROMATIC)

Symbols Xn Risk Phrases 65, 10

2.5-10 % 2-BUTOXYETHANOL / ETHYLENE GLYCOL MONOBUTYL ETHER

Symbols Xn,Xi Risk Phrases 20/21/22, 36/38

Symbols Key - T=Toxic Xn=Harmful C=Corrosive Xi=Irritant E=Explosive O=Oxidising F+=Extremely Flammable

F=Highly Flammable N=Environmentally Hazardous

Details of Risk Phrases

R10 Flammable

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed

R36/38 Irritating to eyes and skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

R65 Harmful: may cause lung damage if swallowed.

3. HAZARDS IDENTIFICATION

HAZARDS

Harmful

RISKS

Flammable

Harmful by inhalation

Irritating to eyes, respiratory system and skin.

SAFETY ADVICE

Use only in well ventilated areas.

Keep container in a well ventilated place

Keep away from sources of ignition - No smoking

Use only in well ventilated areas.

4. FIRST AID MEASURES

ACTION ON INHALATION - Remove to fresh air, keep warm and at rest. If breathing is irregular or stopped give artificial respiration. Give nothing by mouth. If unconscious place in recovery position and seek medical advice. **ASPIRATION**

HAZARD (entry of stomach contents into the lungs) take immediately to hospital or obtain immediate medical attention.

ACTION ON SKIN CONTACT - Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.

ACTION ON EYE CONTAMINATION - Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 mins. holding the eyelids apart, seek medical advice.

ACTION ON SWALLOWING - If accidentally swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

GENERAL FIRST AID ADVICE - In all cases of doubt or when symptoms persist seek medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

RECOMMENDED EXTINGUISHING MEDIA - Carbon-Dioxide, Dry Powder, Sand.

DO NOT USE - Water.

FIRE FIGHTING INSTRUCTIONS - Fire will produce smoke containing hazardous products of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with a water spray. Do not allow run off from fire fighting to enter drains or water courses.

6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid breathing vapours. Refer to protective measures listed in sect. 7&8. Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth and place in suitable container for disposal in accordance with the waste regulations. Clean preferably with a detergent, avoid use of solvents. Do not allow to enter drains or water courses. If it does the local water company should be contacted immediately, in case of contamination of streams rivers or lakes the National Rivers Authority

7. STORAGE AND HANDLING

STORAGE PRECAUTIONS - If designated flammable is subject to the Highly Flammable Liquids & Liquefied Petroleum Gases Regulations. Up to 50lts may be kept in workroom fireproof cupboard or bin, otherwise in a separate room. Observe the label precautions. Store between 5 & 25°C in a dry well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. Store away from oxidising agents and strongly alkaline and acidic materials.

HANDLING PRECAUTIONS - Vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent creation of explosive or flammable mixtures and avoid vapour concs higher than the OEL. Do not use in areas where potential sources of ignition exist. Electrical equipment should be protected to the appropriate standard. Use non sparking tools & exclude sources of heat, sparks & flames. Avoid skin & eye contact. For personal protection see Sect.8. Good housekeeping and regular removal of waste materials will minimise risks. Keep container tightly closed. Never use pressure to empty, container is not a pressure vessel. Always keep in containers made of the same material as the supply container.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMITS

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT OEL's are as mist

Long Term: 5 mgm/m³

Short Term: 10 mgm/m³

Notation OES

SOLVENT NAPHTHA (LIGHT AROMATIC)

Long Term: 200 mgm/m³

Notation OES

2-BUTOXYETHANOL / ETHYLENE GLYCOL MONOBUTYL ETHER

Long Term: 25 ppm

Short Term: 50 ppm

Notation Sk OES

NOTES - Sen =Respiratory Sensitizer

OES = Occupational Exposure Standard

MEL = Maximum Exposure Limit

OEL's are from EH40 except where marked SUP which are assigned by the supplier of the substance

ENGINEERING PRECAUTIONS - Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If extraction methods are insufficient to maintain concentrations of particulates and/or solvent vapours below relevant OEL's, suitable respiratory protective equipment should be worn.

GENERAL PRECAUTIONS - All ppe, including rpe, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH regulations. Hygiene measures: keep away from food, drink and animal feeding stuffs. Wash hands before breaks and at the end of workday.

RESPIRATORY PROTECTION - Air fed respiratory equipment should be worn when sprayed if levels cannot be controlled below OEL's and engineering methods cannot be reasonably improved.

HAND PROTECTION - Full physical protection is best. Seek relevant advice from glove manufacturers. Barrier cream may be of help but should not be applied after exposure has occurred.

EYE PROTECTION - Eye protection designed to protect against liquid splashes should be worn.

SKIN PROTECTION - Cotton or cotton/synthetic overalls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap & water or a proprietary skin cleaner.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State - YELLOWISH LIQUID

Flash Point

Specific Gravity - .83

Vapour Density - HEAVIER than AIR

Lower Explosion Limit - 0.8% volpar

10. STABILITY AND REACTIVITY

Stable under the recommended storage & handling conditions (see Sect.7). In a fire, hazardous decomposition products such as smoke, carbon monoxide, carbon dioxide, and oxides of nitrogen may be produced. Keep away from oxidising agents and strongly alkaline and acid materials to prevent the possibility of an exothermic reaction.

11. TOXICOLOGICAL INFORMATION

Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and respiratory system and adverse effects on the renal and central nervous systems. Symptoms include headaches, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases unconsciousness. Splashes in the eyes may cause irritation and reversible local damage. Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin. Splashes in or contamination of the eye may cause irritation and reversible local damage. There is no data available on the product itself.

12. ECOLOGICAL INFORMATION

There is no data available on the product itself. The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution (1974) & Environmental Protection (1990) Acts. Using the information in this data sheet, advice should be obtained from the Waste Regulation Authority whether the Special Waste Regulations 1980 apply.

14. TRANSPORT INFORMATION

UN No - 1993

Class - 3

Designation - FLAMMABLE LIQUID

For Transport Information other than UK Road or Rail please contact your supplier.

REGULATORY INFORMATION

CLASSIFICATION

Harmful

CONTAINS

RISKS PHRASES

Flammable

Harmful by inhalation

Irritating to eyes, respiratory system and skin.

SAFETY PHRASES

Use only in well ventilated areas.

Keep container in a well ventilated place
Keep away from sources of ignition - No smoking
Use only in well ventilated areas.

16. OTHER INFORMATION

Date of Origination - 15/03/96

Date of Last Revision - 26/07/00

Reason for Revision -

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemicals (Hazard Information & Packaging) Regulations. The product should not be used for purposes other than those shown in sect.1 without first referring to the supplier and obtaining written instructions. As the specific conditions of use of the product are outside of the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information contained in this Safety Data Sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in:-

The Control Of Substances Hazardous to Health Regulations 1988 (SI 1988: 1657)

The Manual Handling Operations Regulations 1992 (SI 1992: 2793)

Storage of Flammable Liquids in Containers. HS(G)51

Storage of Packaged Dangerous Substances. HS(G)71

The Environmental Protection (Duty of Care) Regulations 1992 (SI 1988: 2839)