



## SAFETY DATA SHEET

### Fusor 108B/109B Part A

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

**PRODUCT NAME** Fusor 108B/109B Part A  
**PRODUCT NO.** 54100RG  
**SUPPLIER** Lord Corporation (Europe) Ltd  
 Chemical Products Division  
 Stretford Motorway Estate, Barton Dock  
 Road  
 Stretford, Manchester. M32 0ZH. United  
 Kingdom  
 +44 (0)161 865 8048  
 +44 (0)161 865 0096

#### 2 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
CYCLOHEXYL METHACRYLATE		101-43-9	1-5%	Xi;R36/37/38.
HEMA PHOSPHATE		52628-03-2	1-5%	Xi;R36/38.
METHACRYLIC ACID	201-204-4	79-41-4	1-5%	C;R35 Xn;R21/22
METHYL METHACRYLATE	201-297-1	80-62-6	30-60%	F;R11 R43 Xi;R37/38
N,N-DIMETHYLANILINE	204-493-5	121-69-7	< 1%	Carc3;R40 T;R23/24/25 N;R51,R53

The Full Text for all R-Phrases are Displayed in Section 16

#### 3 HAZARDS IDENTIFICATION

Highly flammable. May cause sensitisation by skin contact. Irritating to eyes, respiratory system and skin.

CLASSIFICATION Xi;R36/37/38. R43. F;R11.

#### 4 FIRST-AID MEASURES

##### GENERAL INFORMATION

Remove affected person from source of contamination. Move the exposed person to fresh air at once. Provide rest, warmth and fresh air. Get medical attention.

##### INHALATION

Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

##### INGESTION

DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Immediately rinse mouth and provide fresh air. Get medical attention immediately! NOTE! Keep affected person away from heat, sparks and flames!

##### SKIN CONTACT

Remove affected person from source of contamination. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing.

##### EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

#### 5 FIRE-FIGHTING MEASURES

## Fusor 108B/109B Part A

### EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Dry chemicals, sand, dolomite etc. Carbon dioxide (CO<sub>2</sub>). Water spray, fog or mist.

### SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to flames with water until well after the fire is out. Keep run-off water out of sewers and water sources. Dike for water control.

### UNUSUAL FIRE & EXPLOSION HAZARDS

HIGHLY FLAMMABLE! Vapours are heavier than air and may spread near ground to sources of ignition.

## 6 ACCIDENTAL RELEASE MEASURES

### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet.

### ENVIRONMENTAL PRECAUTIONS

Do not discharge into drains, water courses or onto the ground.

### SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Stop leak if possible without risk. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb in vermiculite, dry sand or earth and place into containers.

## 7 HANDLING AND STORAGE

### USAGE PRECAUTIONS

Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

### STORAGE CLASS

Flammable liquid storage.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m <sup>3</sup>	ST - ppm	ST - mg/m <sup>3</sup>
METHYL METHACRYLATE	OES	50 ppm	208 mg/m <sup>3</sup>	100 ppm	416 mg/m <sup>3</sup>
METHACRYLIC ACID	OES	20 ppm	72 mg/m <sup>3</sup>	40 ppm	143 mg/m <sup>3</sup>
N,N-DIMETHYLANILINE	OES	5 ppm(Sk)	25 mg/m <sup>3</sup> (Sk)	10 ppm(Sk)	50 mg/m <sup>3</sup> (Sk)

### INGREDIENT COMMENTS

OES = Occupational Exposure Standard.

### PROTECTIVE EQUIPMENT



### ENGINEERING MEASURES

Explosion-proof general and local exhaust ventilation. All handling to take place in well-ventilated area.

### RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit

### HAND PROTECTION

Use protective gloves. SPECIFIC RECOMMENDATIONS. Neoprene. Nitrile.

### EYE PROTECTION

Wear approved safety goggles. Use safety goggles and face shield in case of splash risk.

### OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## Fusor 108B/109B Part A

### HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Paste		
COLOUR	White / off-white		
ODOUR	Sweetish		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	1.23 @ 20 °c	FLASH POINT (°C)	16 Sh CC (Setaflash closed cup).

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

### MATERIALS TO AVOID

Amines. Strong acids. Strong alkalis. Strong oxidising substances.

### HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Oxides of: Nitrogen.

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

May cause irritation to the respiratory system.

### INGESTION

Harmful if swallowed.

### SKIN CONTACT

Irritating to skin. May cause sensitisation by skin contact.

### EYE CONTACT

Irritating to eyes.

### HEALTH WARNINGS

This product has low toxicity. Only large volumes may have adverse impact on human health.

### ROUTE OF ENTRY

Inhalation. Skin and/or eye contact. Ingestion.

### TARGET ORGANS

Respiratory system, lungs. Skin. Eyes.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

No data on possible environmental effects have been found.

## 13 DISPOSAL CONSIDERATIONS

### GENERAL INFORMATION

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

## 14 TRANSPORT INFORMATION

**Fusor 108B/109B Part A**



UK ROAD CLASS	3		
PROPER SHIPPING NAME	ADHESIVES		
UN NO. ROAD	1133	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	HAZARD No. (ADR)	33
ADR LABEL NO.	3	HAZCHEM CODE	3YE
CEFIC TEC(R) NO.	30GF1-I+II,30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1133
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	II	EMS	F-E, S-D
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1133	ICAO CLASS	3
AIR PACK GR.	II		

**15 REGULATORY INFORMATION**

**LABELLING**



Irritant



Highly Flammable

**CONTAINS**

METHACRYLIC ACID  
METHYL METHACRYLATE

**RISK PHRASES**

R11 Highly flammable.  
R43 May cause sensitisation by skin contact.  
R36/37/38 Irritating to eyes, respiratory system and skin.

**SAFETY PHRASES**

S9 Keep container in a well-ventilated place.  
S16 Keep away from sources of ignition - No smoking.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S37 Wear suitable gloves.  
S51 Use only in well-ventilated areas.  
S24/25 Avoid contact with skin and eyes.  
S60 This material and its container must be disposed of as hazardous waste.

**EU DIRECTIVES**

System of specific information relating to Dangerous Preparations. 2001/58/EEC. Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC.

**STATUTORY INSTRUMENTS**

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

**APPROVED CODE OF PRACTICE**

Classification and Labelling of Substances and Preparations Dangerous for Supply. Safety Data Sheets for Substances and Preparations.

**GUIDANCE NOTES**

Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

## Fusor 108B/109B Part A

### 16 OTHER INFORMATION

#### INFORMATION SOURCES

Dangerous Properties of Industrial Materials Report, N.Sax et.al.

REVISION DATE 01/11/04

REV. NO./REPL. SDS GENERATED 02-10/10/02

SDS NO. LC35-FUSOR 108B/109B PART A-03-01/11/04

#### RISK PHRASES IN FULL

R11	Highly flammable.
R21/22	Harmful in contact with skin and if swallowed.
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R35	Causes severe burns.
R36/37/38	Irritating to eyes, respiratory system and skin.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R37/38	Irritating to respiratory system and skin.
R40	Limited evidence of a carcinogenic effect.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.